



ENPAC, LLC CERTIFICATION

September 23, 2025

NOTICE NO: 3823-1220

PRODUCT: Poly-Overpack 20 Salvage Drum "X" Rating (ENPAC Part No. 1220-Standard colors)

MANUFACTURER AND TESTING FACILITY: ENPAC, LLC 34355 Melinz Parkway, Eastlake, Ohio 44095

REGULATION: United Nations General Recommendation on Packing for Transportation of Dangerous Goods, 49 CFR §173.3 and 49 CFR §178.601.

ITEMS TESTED: One (1) sample lot of removable, open head, plastic non-bulk packagings.

Packaging type:	1H2	Closure type:	Screw on lid
Manufacturing method	Injection molded	Manufacturing method	Injection molded
Material of Body:	High impact copolymer polypropylene	Material of closure:	High impact copolymer polypropylene
Rated capacity (l)/(gal):	75.7 l / 20.0 gal.	Closure diameter (cm)/(in):	58.09 cm / 22.87 in.
Overflow capacity (l)/(gal):	83.62 l / 22.09 gal.	Closure height (cm)/(in):	12.07 cm / 4.75 in.
Tare weight-body (kg)/(lb.):	2.72 kg / 6.00 lb.	Tare weight (closure assembly) (kg)/(lb.):	1.91 kg / 4.20 lb. (Lid & Gasket)
Overall diameter (cm)/(in):	56.52 cm / 22.25 in.		
Overall height (cm)/(in):	43.51cm / 17.13 in.		

CONCLUSION: Part design complies and passes all required testing and pertinent regulations as specified in 49 CFR §171 thru 49 CFR §180, and is therefore ENPAC, LLC Certified. Packagings must be filled and used in accordance with all pertinent DOT and UN regulations. Failure to do so renders the qualification invalid and voids all warranties implied or stated.

PACKAGING MARKINGS:



1H2/X75/S/YY/USA/M6100

YY=Year of Manufacture

APPROVED BY:

(MANAGING MEMBER)

(QUALITY ASSURANCE MANAGER)