



# ENPAC, LLC CERTIFICATION

## June 18<sup>th</sup>, 2025

**NOTICE NO:** 3794-1230

**PRODUCT:** Poly-Overpack 30 Salvage Drum "X" Rating (ENPAC Part No. 1230-Standard colors)

**MANUFACTURER AND TESTING FACILITY:** ENPAC, LLC 34355 Melinz Parkway, Eastlake, Ohio 44095

**REGULATION:** United Nations General Recommendation on Packing for Transportation of Dangerous Goods, 49 CFR §173.3 and 49 CFR §178.601.

**ITEMS TESTED:** One (1) sample lot of removable, open head, plastic non-bulk packagings.

<b>Packaging type:</b>	1H2	<b>Closure type:</b>	Screw on lid
<b>Manufacturing method</b>	Injection molded	<b>Manufacturing method</b>	Injection molded
<b>Material of Body:</b>	High impact copolymer polypropylene	<b>Material of closure:</b>	High impact copolymer polypropylene
<b>Rated capacity (l)/(gal):</b>	113.56 l / 30.0 gal.	<b>Closure diameter (cm)/(in):</b>	58.06 cm / 22.86 in.
<b>Overflow capacity (l)/(gal):</b>	131.85 l / 34.83 gal.	<b>Closure height (cm)/(in):</b>	11.76 cm / 4.63 in.
<b>Tare weight-body (kg)/(lb.):</b>	3.93 kg / 8.66 lb.	<b>Tare weight (closure assembly) (kg)/(lb.):</b>	1.94 kg / 4.29 lb. (Lid & Gasket)
<b>Body diameter (cm)/(in):</b>	56.46 cm / 22.23 in.		
<b>Body height (cm)/(in):</b>	71.45 cm / 28.13 in.		

**CONCLUSION:** Part design complies and passes all required testing and pertinent regulations as specified in 49 CFR §171 thru 49 CFR §180, and is therefore ENPAC, LLC Certified. Packagings must be filled and used in accordance with all pertinent DOT and UN regulations. Failure to do so renders the qualification invalid and voids all warranties implied.

**PACKAGING MARKINGS:**



1H2/X100/S/YY/USA/M6100

YY=Year of Manufacture

**APPROVED BY:**

(MANAGING MEMBER)

(QUALITY ASSURANCE MANAGER)